

ORTAC METAL ACCESSORIES



METAL BLIND STOPS BRASS


TECHNICAL DETAILS

Material

Screw plug	: Brass with nickel plated
O-ring	: NBR
Connection thread	: Metric (EN60423) / PG (DIN 40430)
Certificates	: ROHS, CE, PT, TUV, TURK LOYDU
Protection class	: IP68

Properties

For unused threaded holes
Assembling with screwdriver
For machine and equipment manufacturing
For electric motor manufacturing



PİRİNÇ KÖRTAPA

Hammaddesi	: Piring, nikel kaplı
Bağlantı dişi M	: EN 60423
Bağlantı dişi PG	: DIN 40430
Koruma sınıfı	: IP68
O-ring	: Nitril kauçuk

METRIC/PG THREAD BLIND STOPS

AG Thread	Code	H mm	GL mm	D mm	p. 68
M 12 x 1,5	OMBK 01	7,5	5	14	
M 16 x 1,5	OMBK 02	8	5	18	
M 20 x 1,5	OMBK 03	9,5	6,5	22	
M 25 x 1,5	OMBK 04	11	7	28	
M 32 x 1,5	OMBK 05	12	8	35	
M 40 x 1,5	OMBK 06	13	8,5	44	
M 50 x 1,5	OMBK 07	15	9	54	
M 63 x 1,5	OMBK 08	16	10	67	
PG 7	OPBK 01	8	5	14	
PG 9	OPBK 02	9	6	17	
PG 11	OPBK 03	9	6	20	
PG 13,5	OPBK 04	9,5	6,5	22	
PG 16	OPBK 05	9,5	6,5	24	
PG 21	OPBK 06	11	7	30	
PG 29	OPBK 07	12	8	39	
PG 36	OPBK 08	15	9	50	
PG 42	OPBK 09	16	10	57	
PG 48	OPBK 10	16	10	64	

PRODUCT RANGE OVERVIEW