




ORvent®



VENTILATION PLUGS BRASS

TECHNICAL DETAILS

Material

Cap & body

: Brass nickel plated

Washer

: NBR / EPDM

Vent Part

: Acrylic Co-Polymer on Nylon Support
(Hydrophobic-Oleophobic)

Connection thread

: Metric (EN 60423)

Certificates

: ROHS,CE,PT,TUV

Protection class

: IP68

Temperature range

: -20 °C +100 °C -30 +150 °C (short term)

Benefits

- Balance the pressure inside and outside of your systems
- Prevents corrosion and water condensation inside the enclosure
- Extend the lifetime of your product
- Various air flows
- Easy to assemble
- High chemical resistance

Applications

- Industrial and electronic applications
- Wind & Solar applications
- Lighting Industry
- Automotive & Automation technology
- Railway industry

VENTILATION PLUGS

PRODUCT RANGE OVERVIEW

AG Thread	Code	H mm	GL mm	 mm	Thread Diameter mm	Hole Diameter mm	Average Air Flow l/H	Water Intrusion bar
M 4 x 0,70	OMBVP4UH	10	3	12	4	4,2	70	0,1
M 8 x 1,25	OMBVP8UH	13	6	12	8	8,2	70	0,1
M 10 x 1,5	OMBVP10UH	13	6	12	10	10,2	70	0,1
M 12 x 1,5	OMBVP01S	14	6	17	12	12,3	16	0,8
M 12 x 1,5	OMBVP01M	14	6	17	12	12,3	25	0,5
M 12 x 1,5	OMBVP01H	14	6	17	12	12,3	150	0,2
M 12 x 1,5	OMBVP01UH	14	6	17	12	12,3	300	0,1
M 12 x 1,5	OMBVP01SL	18	10	17	12	12,3	16	0,8
M 12 x 1,5	OMBVP01ML	18	10	17	12	12,3	25	0,5
M 12 x 1,5	OMBVP01HL	18	10	17	12	12,3	150	0,2
M 12 x 1,5	OMBVP01UHL	18	10	17	12	12,3	300	0,1
M 16 x 1,5	OMBVP02S	18	10	19	16	16,3	16	0,8
M 16 x 1,5	OMBVP02M	18	10	19	16	16,3	25	0,5
M 16 x 1,5	OMBVP02H	18	10	19	16	16,3	150	0,2
M 16 x 1,5	OMBVP02UH	18	10	19	16	16,3	300	0,1