

## TACFLEX PVC SPIRAL CONDUITS






## PLASTIC SPIRAL CONDUITS PVC

### TECHNICAL DETAILS

Material	: PVC
Certificates	: CE, TUV
Color	: Gray Code (RAL7035)
Temperature range	: -5 °C +70 °C
Standard	: EN50086-1 (CEI 23-29) : EN50086-2-3 (CEI 23-56) : EN613086-1-2-3
Compression resistance	: 320N

**Properties**  
30 mt. Roll length



### PVC SİRAL BORU

Hammaddesi	: Sert PVC
Renk	: RAL 7035 (Gri)
İzolasyona dayanıklılık	: > 100 MΩ
Basınca dayanıklılık	: 350 N
Sürekli ısıya direnci	: -5 °C + 70 °C
Referans standartları	: EN50086-1 (CEI 23-29) EN50086-2-3 (CEI 23-56) IEC EN61386-1-2-3

### PVC SPIRAL CONDUITS

PRODUCT RANGE OVERVIEW

Gray Code ■ RAL 7031	d Ø mm.	d1 Ø mm.	Roll Length mt.
GGX 8	8	12	30
GGX 10	10	14,5	30
GGX 12	12	16,3	30
GGX 14	14	18,6	30
GGX 16	16	20,5	30
GGX 18	18	20	30
GGX 20	20	24,7	30
GGX 22	22	27	30
GGX 25	25	30,3	30
GGX 28	28	33,2	30
GGX 32	32	37,5	30
GGX 35	35	40,5	30
GGX 38	38	44,1	30
GGX 40	40	46,2	30
GGX 50	50	57	30