



tacflex



RJ-45 CABLE GLANDS BRASS - POLYAMIDE


TECHNICAL DETAILS

Material

Cap nut	: Polyamide PA6 V2 / Brass with nickel plated
Sealing ring	: TPV (special seal for RJ-45 cables)
Gland body	: Polyamide PA6 V2 / Brass with nickel plated
O-ring	: NBR (optional)
Connection thread	: Metric (EN 60423) / PG (DIN 40430)
Protection class	: IP68
Temperature	: -20 °C +100 °C -30 °C +150 °C (short term)
Certificates	: ROHS, CE, PT, TUV

Benefits

Designed and produced to use with RJ-45 cables
Various seal options (multiholes)
For wide cable range
Easy to assemble
Halogen free



AG Thread	Gray Code	L. Gray Code	Black Code	H mm.	GL mm.	B mm.	C mm.	A mm.
PG 13,5	ORG04-SR05	ORL04-SR05	ORB04-SR05	29	9	24	24	5
PG 16	ORG05-SR05	ORL05-SR05	ORB05-SR05	33	9	27	27	5
PG 21	ORG06-SR05	ORL06-SR05	ORB06-SR05	38	11	33	33	5
PG 21	ORG06A5-SR	ORL06A5-SR	ORB06A5-SR	38	11	33	33	2x5
PG 21	ORG06B5-SR	ORL06B5-SR	ORB06B5-SR	38	11	33	33	3x5
PG 29	ORG07-SR05	ORL07-SR05	ORB07-SR05	41	11	42	42	5
M 20	OMRG04-SR05	OMRL04-SR05	OMRB04-SR05	29	10	24	24	5
M 20	OMRG05-SR05	OMRL05-SR05	OMRB05-SR05	33	10	27	27	5
M 25	OMRG06-SR05	OMRL06-SR05	OMRB06-SR05	38	10	33	33	5
M 25	OMRG06A5-SR	OMRL06A5-SR	OMRB06A5-SR	38	10	33	33	2x5
M 25	OMRG06B5-SR	OMRL06B5-SR	OMRB06B5-SR	38	10	33	33	3x5
M 32	OMRG07-SR05	OMRL07-SR05	OMRB07-SR05	41	10	42	42	5

BRASS CABLE GLANDS

PG 13,5	OPBG04-SR05	26,5	6,5	22	22	5
PG 16	OPBG05-SR05	28	6,5	24	24	5
PG 21	OPBG06-SR05	31,5	7	30	30	5
PG 21	OPBG06A5-SR	31,5	7	30	30	2x5
PG 21	OPBG06B5-SR	31,5	7	30	30	3x5
PG 29	OPBG07-SR05	38	8	40	40	5
M 20	OMBG03-SR05	26,5	8	22	22	5
M 25	OMBG04-SR05	28	8	27	24	5
M 32	OMBG05-SR05	31,5	9	34	34	5
M 32	OMBG05A5-SR	31,5	9	34	34	2x5
M 32	OMBG05B5-SR	31,5	9	34	34	3x5
M 40	OMBG06SR05	38	9	43	40	5