


## FLEXIBLE SPIRAL CONDUITS PVC COATED METAL

### TECHNICAL DETAILS

Material	: Galvanised steel PVC coated
Certificates	: ROHS, CE, PT, TUV
Color	: Black (RAL9005) Other color versions are available on request with reasonable qty.
Protection class	: IP54, IP65
Temperature range	: -15 °C +70 °C

### Properties

High fatigue life  
High impact strength  
Self-extinguishing  
High UV resistance (black) (on request)  
Full-shrink packing



Code	Size	d mm.	d1 mm.	Roll Length mt.
OPCGS 7	-	7,5	11,5	50
OPCGS 9	1/4"	9	13	50
OPCGS 11	3/8"	11	15	50
OPCGS 13	3/8"	13	16,5	50
OPCGS 14	-	14	18	50
OPCGS 16	1/2"	16	20	50
OPCGS 18	-	18	22	50
OPCGS 21	3/4"	21	25	50
OPCGS 26	1"	26	31	25
OPCGS 29	-	29	34	25
OPCGS 32	-	32	37	25
OPCGS 35	1 1/4"	35	40	25
OPCGS 37	-	37	42	25
OPCGS 40	1 1/2"	40	45	25
OPCGS 42	-	42	47	25
OPCGS 45	-	45	50	25
OPCGS 51	2"	51	56	25
OPCGS 63	2 1/2"	63	68	15
OPCGS 75	3"	75	83	15
OPCGS 100	4"	100	107	10