

ORTAC METAL CABLE GLANDS SERIES



METAL CABLE GLANDS SPECIAL TYPE BRASS


TECHNICAL DETAILS

Material

Cap nut	: Brass with nickel plated
Sealing ring	: EPDM - TPV
Gland body	: Brass with nickel plated
O-ring	: NBR
Connection thread	: Metric (EN60423)
Certificates	: ROHS, CE, PT, TUV, TÜRK LOYDU
Protection class	: IP68
Temperature range	: -20 °C +100 °C -40 °C +150 °C

Properties

High impact and temperature resistance
Easy to assemble
For wide cable range
XL cables



ÖZEL BOY ETANJ PİRİNÇ RAKOR

Hammaddesi	: Pirinç, nikel kaplı
Bağlantı dişi M	: EN 60423
Koruma sınıfı	: IP68 - 5 bar
Isiya direnci	: -20 °C + 100 °C -40 °C + 150 °C
Conta	: EPDM (Etilen-Propilen-Dien-Monomer TPV)
O-ring	: Nitril kauçuk

SPECIAL TYPE CABLE GLANDS

AG Thread	Code	H mm	GL mm	B mm	C mm	A mm
M 63 x 1,5	OMBG 17	48	15	70	75	45 - 55
M 75 x 1,5	OMBG 18s	48	20	85	75	45 - 55
M 75 x 1,5	OMBG 18	58	20	90	90	50 - 63
M 80 x 2,0	OMBG 1880	58	20	90	90	50 - 63
M 90 x 2,0	OMBG 19	61	20	100	100	60 - 70
G 2 ½"	ONBG 18s	48	20	85	75	45 - 55
G 2 ½"	ONBG 18	58	20	90	90	50 - 63
G 3"	ONBG 19	61	20	100	100	60 - 70

IP 68

Halogen free

PRODUCT RANGE OVERVIEW

* Special sizes available on request.